

Order no.: 154046

**Mobile scaffolding,
0.75 × 1.80 m, with
outrigger. Platform height
10.35 m**

Accessories for the product family



Order no.: 027992

**Safety railing for
mobile scaffolding**



Order no.: 027904

**Push-fit frame
75/196**



Order no.: 027955

**Railing lengthwise
1,800 mm**



Order no.: 027931

**Platform with
trapdoor For
scaffolding length:
1.8 m**



Order no.: 027913

**Toe board front
side For scaffolding
width: 0.75 m**



Order no.: 027943

**Toe board long side
For scaffolding
length: 1.8 m**



Order no.: 027937

**Diagonal brace 1.8
m**



Order no.: 027935

**Horizontal strut For
scaffolding length:
1.8 m**



Order no.: 027926

Triangular outrigger



Order no.: 027917

**Swivel castor with
spindle height
adjustable Ø 200
mm**




Order no.: 027940

Step-on bracket



Order no.: 027912

Ballast weight with hanging brackets
RAL 1021



Order no.: 019081

Clip tray for tubes
Ø 50 mm



Order no.: 027920

Wall spacer adjustable
Adjustable up to 1.0 m



Order no.: 070506

Frame extension
can be clamped on
Adjustment range
max. 400 mm



Order no.: 019274

Storage tray 500 x 220 mm
Clamping
range 38–51 mm



Order no.: 019276

Storage tray 800 x 300 mm
Clamping
range 38–51 mm



Order no.: 019175

Inspection sticker
40 x 40 mm



Order no.: 019176

Inventory sticker



Order no.: 070507

Safety door on front side
Push-fit
frame 0.75



Order no.: 070505

Scaffolding connector set
For scaffolding width:
0.75 m



Order no.: 019136

Spring clip for mobile scaffolding
with short pin,
closed



Order no.: 019137

Spring clip for mobile scaffolding
with long pin, open



Order no.: 070524

Scaffolding strut telescopic
1,700–
2,500 mm



Order no.: 027104

Height-adjustable spindle



Order no.: 027922

Swivel castor with spindle, non-marking grey height adjustable Ø 200 mm



Order no.: 027921

Swivel castor with spindle, electrically conductive height adjustable Ø 200 mm



Order no.: 027958

Swivel castor Ø 200 mm With parking brake and pin



Order no.: 027905

Push-fit frame 75/112