



Order no.: 033706

Step straight ladder, wood without stabiliser



Number of steps

- 6
- 8
- 10
- 12

Specification

Working height 2.7 m	Step design Steps	Number of steps/rungs 6 steps	Step depth 92 mm	Step/Rung distance 235 mm
Ladder length 1.69 m	Inclination 70 °	Outer width 420 mm	Depth of side-rails 70 mm	Width of side-rails 23 mm
Max. load capacity 150 kg	Design type To lean against	Weight 5.5 kg	Transport dimensions 1685 x 425 x 90 mm, 5.5 kg	Business division MUNK Günzburger Steigtechnik
Order no. 033706	Price € 224.00			

Facts

- Step straight ladder made of wood
- Side-rails and steps made of finger-jointed pine or knot-free Caroline pine
- Grooved steps with a depth of 92 mm
- Steps inserted in side-rail using threaded rod

- Slanted side-rail end for optimum contact with or attachment to walls
- Step spacing: 235 mm
- Ladder width: 420 mm (without stabiliser)
- Ladder inclination: 70°
- Maximum load: 150 kg
- Note: Straight ladders over 3.0 m can be used without a stabiliser only when they are used exclusively for their intended purpose (e.g. permanently installed, fitted with hooks, fastened with a belt)

Scope of supply

- Ladder: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic

- No health hazards for the users

More product pictures



Added value

Retrofit stabiliser

Safe, standards-compliant ascent

- For retrofitting existing ladders with ladder lengths over 3.0 m in compliance with standards
- Non-slip ladder shoes
- Available in different widths




Industrial grade

- Sturdy processing for demanding applications (e.g. 4-fold edging)
- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories

Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on [TRBS 2121 Part 2](#) has been summarised on our Service page
- Read our [tips and tricks](#) on how to calculate [working height](#)



Corporate certifications

on sustainability criteria



Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID 9108612548



Nachhaltigkeit

EcoVadis
sustainable supply management

CSR-Rating in Silber 2022

