



Step stepladder insert





Specification

Suitable for 040270	Product type Accessories	Max. load capacity 150 kg	Height 1.17 m	Depth of side-rails 73 mm
Width of side-rails 25 mm	Step depth 80 mm	Suitable for ladder type Double-sided ladders	Material Aluminium coated	Transport dimensions 870 x 471 x 160 mm, 7 kg
Business division MUNK Günzburger Steigtechnik	Order no. 040260	Spare part for article no.		

Facts

- Flexible extension of the stepladder pluggable
- Easy and fast installation, thanks to push-fit connectors with hook lock
- Space-saving transport and storage
- Note: Heights and step lengths measured in combination with the stepladder-stepladder (order no. 040270)



Scope of supply

Push-fit section: ascending part: 2 x

Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users



More product pictures









Added value

Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories





Corporate certifications

on sustainability criteria







