



Order no.: 115442

Telescopic ladder blue DIN EN 1147

Specification

Rescue height	Intended use	Ladder length	Ladder length retracted	Ladder length extended
3.1 m	Rescue	4.4 m	910 mm	4.4 m
Setting angle 70 °	Clear width between rungs 270 mm	Depth of side-rails 100 mm	Width of side-rails 80 mm	Step/Rung height 28 mm
Step depth	Number of steps/rungs	Max. load capacity	Persons max.	Material
29 mm	14 rungs	216 kg	2	Aluminium
Transport dimensions 940 x 560 x 130 mm, 14.5 kg	Business division MUNK Rettungstechnik	Order no. 115442		

Facts

- Aluminium telescopic ladder
- Rescue ladder compliant with DIN EN 1147
- Abrasion-resistant anodised octagonal tube side-rails



- With heat-insulating, non-slip plastic coating (DE and THW (Federal Agency for Technical Relief) designs)
- Variable height adjustment via intuitive telescopic function (partial heights possible)
- Safety system for controlled retraction
- Minimises the risk of crushing and injury
- Permissible load: 250 kg / 2 people
- These products are covered by the statutory warranty

Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users



More product pictures







Corporate certifications

on sustainability criteria







