

Order no.: REF-7312847

Hinged access ramp



Specification

| | | | | |
|--------------------------|-----------------------------|------------------------------------|-----------------|--|
| Length 1.45 m | Total length max. 1.76 m | Extendable No | Foldable Yes | Total width 212 mm |
| Material Aluminium | Material thickness 60 mm | Surface Aluminium corrugated | Mobile No | Business division MUNK Rettungstechnik |
| Order no. REF-7312847 | | | | |

Facts

- Compact access ramp made of aluminium
- Non-slip covering made of grooved aluminium
- For easy and safe loading and unloading of vehicles and trailers
- With side toe boards
- Total length folded in approx. 1,500 mm
- Total length folded out approx. 3,000 mm
- Total width approx. 200 mm

- Maximum load: 250 kg

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Corporate certifications

on sustainability criteria



Management
System
ISO 9001:2015
ISO 14001:2015

www.tuv.com
ID 9108612548



Nachhaltigkeit

EcoVadis
sustainable supply management

CSR-Rating in Silber 2022