



Order no.: 036382

GFK stepladder with  
nivello® crossbeam

Number of steps

12

14

Specification

|                                                        |                                                      |                                   |                                |                            |
|--------------------------------------------------------|------------------------------------------------------|-----------------------------------|--------------------------------|----------------------------|
| Working height<br>4.1 m                                | Step design<br>Steps                                 | Number of steps/rungs<br>12 steps | Step width<br>370 mm           | Step depth<br>80 mm        |
| Step/Rung distance<br>235 mm                           | Ladder length<br>3.17 m                              | Inclination<br>70 °               | Outer width<br>420 mm          | Stabiliser width<br>930 mm |
| Depth of side-rails<br>73 mm                           | Width of side-rails<br>25 mm                         | Max. load capacity<br>150 kg      | Design type<br>To lean against | Weight<br>14.5 kg          |
| Transport dimensions<br>3168 x 421 x 74 mm,<br>14.5 kg | Business division<br>MUNK Günzburger<br>Steigtechnik | Order no.<br>036382               | Price<br>€ 890.00              |                            |

Facts

- Step straight ladder made of GFRP
- Side-rails and steps made of glass-fibre reinforced plastic profiles (min. 10 years ageing resistance when stored and used as intended)
- Grooved steps with a depth of 80 mm
- By using the metal suspension step, the insulation voltage is reduced to 1,000 V

- High-strength step-to-side-rail connection
- Step spacing: 235 mm
- Ladder width: 420 mm (without stabiliser)
- Stabiliser made of reinforced fibre glass with non-slip ladder shoes in optimal width for the selected product
- Maximum load: 150 kg
- Ladder inclination: 70°
- Tested according to EN 61478:2002 + A1 (2004), 6.5.1 Category 2: 60,000 V
- Note: Products with GFRP content are non-returnable, due to their sensitivity; the statutory warranty applies (ageing resistance 10 years)

### Scope of supply

- Ladder: 1 x
- Stabiliser (enclosed separately): 1 x

### Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.

- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures

---



## Added value

---

### Fiberglass

Ladders made of GFRP offer the perfect properties for special challenges. [Find out](#) what makes GFRP such a special material, how we use it for ladders and where these ladders are used.



## Corporate certifications

on sustainability criteria



Management  
System  
ISO 9001:2015  
ISO 14001:2015  
  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548

