



Order no.: 031322

Multi-function ladder, 4section, with nivello® stabiliser and wooden surface.



Number of rungs

 $2x2 + 2x3 \quad 2x3 + 2x4$

Specification

Working height 4.8 m	Step design Rungs	Number of steps/rungs 4x 3 rungs	Step/Rung height 30 mm	Step depth 30 mm
Step/Rung distance 280 mm	Ladder length as straight ladder 3.65 m	Ladder length as double- sided ladder 1.76 m	Base spread as double ladder 1.21 m	Inclination 70 °
Height as working platform 990 mm	Length as working platform 1.4 m	Base spread as working platform 2.4 m	Outer width 350 mm	Stabiliser width 930 mm
Depth of side-rails 58 mm	Width of side-rails 25 mm	Max. load capacity 150 kg	Transport dimensions 1450 x 350 x 450 mm, 18 kg	Business division MUNK Günzburger Steigtechnik
Order no. 031322				

Facts

- Aluminium multi-function rung ladder
- Stable rectangular tube side-rails



- Rectangular rungs grooved on both sides, 30 x 30 mm
- 4-fold edged rung-to-side-rail connection
- Can be used as step and straight ladder and as work platform (required accessories included)
- Optimum operational safety due to six automatically locking steel hinges
- nivello® stabilisers for extra safe stance and ascent (double-sided, enclosed separately)

Rung distance: 280 mm

Ladder width: 350 mm

Maximum load: 150 kg

Scope of supply

Ladder: 1 x

Stabiliser (enclosed separately): 2 x

Wood flooring for use as a work floorboard: 1 x

Instructions for use and operation: 1 x

Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany



- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures





Added value

Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

Corrosion-resistant fixtures

Universal and versatile use

Compact size for transport and storage

Upper ladder can also be used individually (up

- Use of high-quality and high-strength materials
- Versatile and practical accessories



Flexibility

to 3.0 m)

Large range of accessories

The right equipment for every application

 Insertion hooks with lift-off protection or automatically locking steel hinges

with high-strength plastic coating

Optimised guidance, thanks to guide fixtures

- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders



Easy handling

The movable ladder shoe sets new standards in

stability

Learn more



nivello® stabiliser

Extra safe, standards-compliant ascent for straight ladders over 3.0 m

- Extra wide stabiliser for even greater stability
- nivello® ladder shoes with patented 2-axis inclination technology, integrated work angle check and exchangeable foot plates
- Individually available as spare part





roll-bar retrofit kit

- Rolling instead of carrying: ergonomic and convenient handling
- Simple, no-drill mounting on stabilisers
- User-friendly operation without bending down



Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on <u>TRBS 2121 Part 2</u> has been summarised on our Service page
- Read our <u>tips and tricks</u> on how to calculate <u>working height</u>





Corporate certifications

on sustainability criteria







