



Order no.: 930613

Clamping profile black

To fit slot size [mm]

6



Specification

Material Plastics

Weight per metre 22 g/m

Groove size 8 mm

Dimension A 6 m

Order no. 930613

Facts

- For inserting glass, acrylic glass, wood or sheet metal elements into the profile slot
- Available in different lengths. Specify the length you require when you place your order
- Possible thickness of push-fit elements: 1.0–4.5
 mm

Description

The black clamping profile is the ideal solution for inserting glass, acrylic glass, wooden or sheet metal elements into the profile slot. It is available in different lengths and can therefore be adapted perfectly to your needs. The sturdy plastic profile is ideal for assembling elements with a thickness of 1.0–2.5 mm. Versions for slot sizes 6 and 8 are available.

Scope of supply

Clamping profile, cut to the required length (max. 6 m): 1 x

Information on sustainability criteria



Corporate certification: ISO 9001

■ Corporate certification: ISO 14001

■ Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures





Corporate certifications

on sustainability criteria







