

Order no.: 040208

Double-sided stepladder



Number of steps

- 2x3
- 2x4
- 2x5
- 2x6
- 2x7
- 2x8
- 2x9
- 2x10
- 2x12
- 2x14

Specification

|                                                     |                              |                                     |                                                   |                                                    |
|-----------------------------------------------------|------------------------------|-------------------------------------|---------------------------------------------------|----------------------------------------------------|
| Working height<br>2.45 m                            | Step design<br>Steps         | Number of steps/rungs<br>2x 4 steps | Step depth<br>80 mm                               | Step/Rung distance<br>235 mm                       |
| Type of non-slip protection<br>Aluminium corrugated | Height<br>910 mm             | Base spread<br>860 mm               | Inclination<br>70 °                               | Lower outer width<br>460 mm                        |
| Depth of side-rails<br>73 mm                        | Width of side-rails<br>25 mm | Max. load capacity<br>150 kg        | Design type<br>Freestanding   Double-sided access | Transport dimensions<br>990 x 460 x 212 mm, 6.5 kg |
| Business division<br>MUNK Günzburger Steigtechnik   | Order no.<br>040208          |                                     |                                                   |                                                    |

Facts

- Stepladder made of aluminium
- Stable rectangular tube side-rails
- Grooved steps with a depth of 80 mm
- 4-fold edged step-to-side-rail connection
- Conical side-rail guide for safe stance

- nivello® ladder shoes with patented 2-axis inclination technology
- ergo-pad® grip area with clamping mechanism
- 4-fold bolted, solid ladder joint made of aluminium
- Spreader lock with two high-strength polyester straps
- Step spacing: 235 mm
- Ladder inclination: 70°
- Maximum load: 150 kg

### Scope of supply

- Ladder: 1 x

### Information on sustainability criteria

---

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic

- No health hazards for the users

More product pictures



## Added value

---

### Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



### ergo-pad® grip area

For easier and more ergonomic handling at the optimum carrying point



The movable ladder shoe sets new standards in stability

[Learn more](#)



### Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on [TRBS 2121 Part 2](#) has been summarised on our Service page
- Read our [tips and tricks](#) on how to calculate [working height](#)



## Certificates

---



25KFP0049-01 -  
Test Certificate  
"Bauart geprüft"

Valid in



DIN EN 131-1:2019  
DIN EN 131-2:2017  
DIN EN 131-3:2018  
EK5/AK1 17-  
02.4:2021  
PAK-  
ANFORDERUNG  
FÜR GS (PAH  
REQUIREMENT  
FOR GS) AFPS GS  
2019:01 PAK

Corporate certifications

on sustainability criteria



Management  
System  
ISO 9001:2015  
ISO 14001:2015  
  
www.tuv.com  
ID 9108612548



Nachhaltigkeit

EcoVadis  
sustainable supply management

CSR-Rating in Silber 2022