



Order no.: 041106

Single-sided stepladder with castors



Number of steps

3	4	5	6	7	8	9	10	12
14								

Specification

Working height 3.4 m	Step design Steps	Number of steps/rungs 6 steps	Platform included as step Yes	Step depth 80 mm
Step/Rung distance 235 mm	Type of non-slip protection Aluminium corrugated	Height 2.05 m	Platform height 1.38 m	Base spread 1.16 m
Inclination 70 °	Lower outer width 700 mm	Depth of side-rails 73 mm	Depth of side-rails, support 58 mm	Width of side-rails 25 mm
Castor diameter 80 mm	Max. load capacity 150 kg	Design type Freestanding Single-sided access With castors	Transport dimensions 2194 x 691 x 157 mm, 11.5 kg	Business division MUNK Günzburger Steigtechnik
Order no. 041106				

Facts

- Stepladder made of aluminium
- Stable rectangular tube side-rails
- 80 mm deep grooved steps and large platform



- 4-fold edged step-to-side-rail connection
- Conical side-rail guide for safe stance
- nivello® ladder shoes with patented 2-axis inclination technology
- Four self-locking spring-loaded castors (Ø 80 mm)
- 'safe-cap' ladder joint
- Rigid connection through metal struts detachable on both sides
- From seven steps or more: Spreader lock with two high-strength polyester straps
- Practical storage tray with integrated hooks and tool holders

Step spacing: 235 mmLadder inclination: 70°

Maximum load: 150 kg

Scope of supply

Ladder: 1 x

Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting



- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures









Added value

Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



The movable ladder shoe sets new standards in stability

Learn more



ergo-pad® grip area

For easier and more ergonomic handling at the optimum carrying point



Spring-loaded castors

- High stability, easy to change position
- Easy to move the ladder when it is set up
- Self-locking
- Also retrofittable and available as a spare part




Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on <u>TRBS 2121 Part 2</u> has been summarised on our Service page
- Read our <u>tips and tricks</u> on how to calculate <u>working height</u>





Certificates





Corporate certifications

Standards for quality and sustainability









