



Order no.: 050085

Platform ladder



Number of steps

- 4
- 5
- 6
- 7
- 8
- 9
- 10

Specification

|                                                      |                                                         |                                                      |                                     |                              |
|------------------------------------------------------|---------------------------------------------------------|------------------------------------------------------|-------------------------------------|------------------------------|
| Working height<br>3.15 m                             | Step design<br>Steps                                    | Number of steps/rungs<br>5 steps                     | Platform included as<br>step<br>Yes | Platform height<br>1.13 m    |
| Step depth<br>80 mm                                  | Step/Rung distance<br>235 mm                            | Height<br>1.88 m                                     | Base spread<br>1.15 m               | Inclination<br>70 °          |
| Lower outer width<br>640 mm                          | Depth of side-rails<br>73 mm                            | Depth of side-rails,<br>support<br>58 mm             | Width of side-rails<br>25 mm        | Max. load capacity<br>150 kg |
| Design type<br>Freestanding  <br>Single-sided access | Transport dimensions<br>2002 x 635 x 163<br>mm, 11.5 kg | Business division<br>MUNK Günzburger<br>Steigtechnik | Order no.<br>050085                 |                              |

Facts

- Platform ladder made of aluminium
- Stable rectangular tube side-rails
- Grooved steps with a depth of 80 mm
- Large, trapeze-shaped platform (400 / 360 x 425 mm)
- 4-fold edged step-to-side-rail connection

- Conical side-rail guide for safe stance
- Two handrails for safe ascent and descent (enclosed separately)
- 'safe-cap' ladder joint
- ergo-pad® grip area with clamping mechanism
- nivello® ladder shoes with patented 2-axis inclination technology
- Practical storage tray (350 x 200 mm)
- Spreader lock with two high-strength polyester straps
- Step spacing: 235 mm
- Ladder inclination: 70°
- Maximum load: 150 kg

### Scope of supply

- Ladder: 1 x
- Handrail (enclosed separately): 2 x
- Assembly instructions: 1 x

### Information on sustainability criteria

---

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany

- **Recyclability:** Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- **Socially acceptable working conditions in production:** fair wages, gender equality
- **Economical and recyclable packaging:** no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- **No health hazards for the users**

## More product pictures

---



## Added value

---

### Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



The movable ladder shoe sets new standards in stability

[Learn more](#)



### Ladder joint safe-cap

- Smooth ladder joint with large contact surface and sturdy plastic protective cap
- The 6 rivets and thicker wall thickness provide for greater stability and protection at this sensitive point on the ladder, increasing its service life
- The safe-cap protects the ladder when in use, when loading and storing, as well as the contact surfaces, walls, truck loading areas and the joint itself



### ergo-pad® grip area

For easier and more ergonomic handling at the optimum carrying point



## Certificates

---



25KFP0610-01 -  
Test Certificate  
"Bauart geprüft"

Valid in



DIN EN 131-1:2019  
DIN EN 131-2:2017  
DIN EN 131-3:2018  
EK5/AK1 17-  
02.4:2021  
PAK-  
ANFORDERUNG  
FÜR GS (PAH  
REQUIREMENT  
FOR GS) AFPS GS  
2019:01 PAK

Corporate certifications

on sustainability criteria



Management  
System  
ISO 9001:2015  
ISO 14001:2015  
  
www.tuv.com  
ID 9108612548



Nachhaltigkeit

EcoVadis  
sustainable supply management

CSR-Rating in Silber 2022