MUNK
Sicherheit. Made in Germany.

Order no.: 064009

Shaft ladder, glass fibre reinforced plastic, 300 mm clear width

Number of rungs

4 | 5 | 6 | 7 | 8 | **9** | 10 | 11 | 12 | 13 | 14 | 15

Specification

Clear width 300 mm	Ladder length 2.52 m	Number of steps/rungs 9 rungs	Depth of side-rails 58 mm	Width of side-rails 25 mm
Outer width 350 mm	Max. load capacity 150 kg	Material GFRP	Transport dimensions 2525 x 358 x 58 mm, 6 kg	Business division MUNK Günzburger Steigtechnik
Order no. 064009				

Facts

- Clear width 300 mm
- Rectangular side-rails 58 × 25 mm
- Grooved rungs
- Various wall anchors available as accessories

Scope of supply

- Ladder: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures

Added value

Rational modular principle

- Shaft ladders in two widths and various lengths offer the right solution for every project
- Ideal for sewage treatment plants, landfills, retention basins, pump shafts, etc.
- Each individual component in the modular kit system meets the same quality and efficiency requirements
- Use of fall protection with wide design possible

Various material versions

- Depending on the application, shaft ladders made of steel, stainless steel and reinforced fibre glass are available
- Wall anchors and accessories are also available in several materials

Mounting and fastening

- Quick and easy installation of the shaft ladders thanks to the optimised installation system
- Adjustable wall anchors for complex projects additionally facilitate installation
- Suitable accessories available for the different material versions

Entry aids

- Different variants in accordance with DIN standards and German Social Accident Insurance (DGUV) regulations for safe entry and exit
- Available in various materials to match the ladders

Highest quality

- Stable rectangular tube side-rails
- High-strength rung-to-side-rail connection
- Non-slip perforated rungs

Fiberglass

Ladders made of GFRP offer the perfect properties for special challenges. Find out what makes GFRP such a special material, how we use it for ladders and where these ladders are used.

Certificates

24KFP1133-01 - Test Certificate "Bauart geprüft"

Valid in

DIN EN 14396:2004

MUNK
Sicherheit. Made in Germany.

Corporate certifications

on sustainability criteria