



Order no.: 065009

Entry aid, double side-rails, stainless steel

For ladder width [mm]

- 340
- 440

Specification

Outer width 340 mm	Suitable for Shaft ladders	Transport dimensions 1570 x 335 x 90 mm, 5.5 kg	Business division MUNK Günzburger Steigtechnik	Order no. 065009
-----------------------	-------------------------------	-------------------------------------------------------	------------------------------------------------------	---------------------

Facts

- Made of pickled and passivated V4A (1.4571) stainless steel or galvanised steel
- Can be lowered, complete with fixtures for ladder side-rail, 50 x 20 mm
- For ladder widths 340 and 440 mm

Scope of supply

- Entry aid: 1 x
- Assembly instructions: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001

- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Corporate certifications

on sustainability criteria



Management
System
ISO 9001:2015
ISO 14001:2015

www.tuv.com
ID 9108612548



Nachhaltigkeit

EcoVadis
sustainable supply management

CSR-Rating in Silber 2022