



Order no.: 115095

Scaffolding bracket, multifunction ladder, DIN EN 1147

Specification

Max. load capacity 216 kg	Persons max. 2	Material Galvanised steel	Transport dimensions 895 x 285 x 68 mm, 2.5 kg	Business division MUNK Rettungstechnik
Order no. 115095				

Facts

- Aluminium scaffolding bracket
- Suitable for multi-function ladder 115093
- (2x required)
- For setting up a ladder platform with working platform 115099 (not included in scope of delivery)
- Scope of delivery: 2x

Information on sustainability criteria

Corporate certification: ISO 9001



- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures





Corporate certifications

on sustainability criteria



