

Order no.: 600747

Platform stairs 60°, mobile, step width 1,000 mm



Number of steps

4	5	6	7	8	9	10	11	12
13	14	15	16					

Specification

Design type 60°	Surface Aluminium corrugated	Number of steps/rungs 7 steps	Step width 1 m	Step depth 225 mm
Height 2.8 m	Vertical height 1.69 m	Base area 1.74 m	Chassis width 1 m	Business division MUNK Günzburger Steigtechnik
Transport dimensions 3539 x 1200 x 902 mm, 83 kg	Order no. 600747			

Facts

- Mobile platform stairs made of aluminium with inclination 60°
- Step and platform width: 1,000 mm
- Platform length: 460 mm
- Last step (depth: 225 mm) mounted at the same height as the platform (total tread area: 685 mm)
- Standard step and platform surface, grooved aluminium (R 9), optionally also available with other surfaces (see overview on right)
- Handrail on both sides and Ø 40 mm 3-sided platform railing with bolted connecting elements as standard (railing height: 1,100 mm)
- Two Ø 100 mm swivel castors on the ascending sector and two Ø 125 mm fixed castors as chassis bar on the support part guarantee easy relocation, the integrated locking devices (total stop) ensure safe stability
- Easy installation thanks to delivery in pre-assembled modules including assembly instructions
- Maximum load: 1.5 kN/m2, step load 150 kg, total load 300 kg
- Note: The standard version includes connecting parts of galvanised steel, which are suitable for indoor use. At a surcharge, they can also be made of stainless steel, which is recommended for outdoor use
- Production in compliance with the European standard series DIN EN ISO 14122 and DIN EN 131-7
- This product is made to order and cannot be returned

Scope of supply

- Stair module: 1 x
- Swivel castor: 2 x
- Lifting castor: 2 x
- Handrail (enclosed separately): 2 x
- Garde-corps: 3 x
- Installation material: 1 x
- Assembly instructions: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Product configurator

Configuring, enquiring about and ordering individual products could not be easier with our [product configurator](#) for stairs, bridging steps and mobile platform stairs. Simply enter your required dimensions and versions step by step, and a rotating 3D model will appear in real time. To save your configuration and request a quotation requires a login which will be set up for you by our Sales team.



Handrail and railing

- Handrail on one side for screwing into plug-in pockets as standard (height: 1,100 mm)
- At an additional charge, plug-in pockets with quick-release fasteners for easy removal of railing and handrail and railing with filler rods or coverings available



Different widths

- Steps and platforms are available in standard widths of 600, 800 and 1,000 mm
- Special sizes available on request



Safety railing

- Safety doors with fixed sizes or telescopic as protection against falling down
- Alternatively also safety barrier or safety rope available

Top surface

The total tread area depends on the platform length selected. This is made up of the platform length plus the depth of the last step(s) (for bridging steps times two), as these are mounted at the same height



Simple installation

- Delivery in pre-assembled modules including assembly instructions
- Quick assembly thanks to screw connections for struts and support parts as well as plug-in pockets for railings

This is what distinguishes our mobile platform stairs

- Individual planning and production by Günzburger Steigtechnik experts in accordance with customer specifications
- Inclinations of 45° and 60° and widths of 600, 800 and 1,000 mm as standard, special dimensions and deviating inclinations available on request
- Standard step and platform design in grooved aluminium (R 9), optionally also in steel grating (R 12), aluminium grating (R 13), perforated steel cover (R 13), perforated aluminium cover (R 13) or with corundum coating (R 13)
- Handrail on both sides and 3-sided platform railing made of Ø 40 mm tubes with bolted connecting elements as standard (height: 1,100 mm). Plug-in pockets with quick-release fasteners for easy removal of the railing and railings with filler rods or coverings available at an additional charge
- Two Ø 100 mm swivel castors on the ascending sector and two Ø 125 mm fixed castors as a chassis bar on the support part guarantee ease of movement, while the integrated locking devices (total stop) ensure excellent stability
- Various central undercarriages with hand or foot control lever for convenient lifting and lowering of the platform stairs before or after movement
- Side-rails made of strong aluminium sections.
- Maximum load: 1.5 kN / m², step load 150 kg, total load 300 kg
- The delivery from the factory is made in pre-assembled modules for quick and simple assembly in accordance with the enclosed assembly instructions

Safety information

To comply with German product safety legislation, stairs should be equipped with handrails on both sides, and platforms should have fall protection (e.g. safety railing) on all sides. If this is not desired or cannot be implemented, the owner must guarantee equivalent safety.

Corporate certifications

on sustainability criteria



Management System
ISO 9001:2015
ISO 14001:2015

www.tuv.com
ID 9108612548



Nachhaltigkeit

EcoVadis
sustainable supply management

CSR-Rating in Silber 2022