



Order no.: 010310

## Rung straight ladder with nivello® stabiliser



Number of rungs

- 6
- 8
- 10
- 12
- 14
- 16
- 18
- 20
- 24

### Specification

|                                                   |                                                     |                                   |                                |                                                     |
|---------------------------------------------------|-----------------------------------------------------|-----------------------------------|--------------------------------|-----------------------------------------------------|
| Working height<br>4.1 m                           | Step design<br>Rungs                                | Number of steps/rungs<br>10 rungs | Step/Rung height<br>30 mm      | Step depth<br>30 mm                                 |
| Step/Rung distance<br>280 mm                      | Type of non-slip protection<br>Aluminium corrugated | Ladder length<br>3.03 m           | Outer width<br>420 mm          | Stabiliser width<br>930 mm                          |
| Depth of side-rails<br>58 mm                      | Width of side-rails<br>25 mm                        | Max. load capacity<br>150 kg      | Design type<br>To lean against | Transport dimensions<br>3035 x 425 x 70 mm,<br>6 kg |
| Business division<br>MUNK Günzburger Steigtechnik | Order no.<br>010310                                 |                                   |                                |                                                     |

### Facts

- Aluminium rung straight ladder
- Stable rectangular tube side-rails
- Rectangular rungs grooved on both sides, 30 x 30 mm
- 4-fold edged rung-to-side-rail connection
- Rung distance: 280 mm

- Ladder width: 420 mm (without stabiliser)
- Maximum load: 150 kg
- nivello® stabiliser with optimum width for the selected product, ensuring an extra safe stance and ascent thanks to nivello® ladder shoes with 2-axis inclination technology, working angle check and exchangeable foot plates. The stabiliser is enclosed separately and is screwed to the lower end of the rail in two places

### Scope of supply

- Ladder: 1 x
- Stabiliser (enclosed separately): 1 x

### Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



## Added value

---

### nivello® stabiliser

Extra safe, standards-compliant ascent for straight ladders over 3.0 m

- Extra wide stabiliser for even greater stability
- nivello® ladder shoes with patented 2-axis inclination technology, integrated work angle check and exchangeable foot plates
- Individually available as spare part



### roll-bar retrofit kit

- Rolling instead of carrying: ergonomic and convenient handling
- Simple, no-drill mounting on stabilisers
- User-friendly operation without bending down



### Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on [TRBS 2121 Part 2](#) has been summarised on our Service page
- Read our [tips and tricks](#) on how to calculate [working height](#)



## Corporate certifications

on sustainability criteria



Management  
System  
ISO 9001:2015  
ISO 14001:2015  
  
www.tuv.com  
ID 9108612548



**Nachhaltigkeit**

**EcoVadis**  
sustainable supply management

CSR-Rating in Silber 2022