



Order no.: 020418

2-section rung push-up  
extension ladder with  
nivello® stabiliser



Number of rungs

- 2x6
- 2x8
- 2x10
- 2x12
- 2x14
- 2x16
- 2x18

Specification

|                              |                              |                                             |                                                         |                                                      |
|------------------------------|------------------------------|---------------------------------------------|---------------------------------------------------------|------------------------------------------------------|
| Working height<br>10.3 m     | Step design<br>Rungs         | Number of steps/rungs<br>2x 18 rungs        | Step/Rung height<br>30 mm                               | Step depth<br>30 mm                                  |
| Step/Rung distance<br>280 mm | Retracted length<br>5.3 m    | Extended length<br>9.18 m                   | Outer width<br>420 mm                                   | Stabiliser width<br>1.2 m                            |
| Depth of side-rails<br>98 mm | Width of side-rails<br>25 mm | Design type<br>To lean against   2-<br>part | Transport dimensions<br>5292 x 425 x 173<br>mm, 30.2 kg | Business division<br>MUNK Günzburger<br>Steigtechnik |
| Order no.<br>020418          |                              |                                             |                                                         |                                                      |

Facts

- Rung push-up extension ladder made of aluminium
- Stable rectangular tube side-rails
- Rectangular rungs grooved on both sides, 30 x 30 mm
- 4-fold edged rung-to-side-rail connection

- Simple height adjustment from rung to rung thanks to insertion hook with automatically engaging lift-off protection
- Upper ladder from size 2x14 rungs with wall castors
- Corrosion-resistant guide fixtures
- Upper ladders up to 3.0 m with nivello® ladder shoes
- Rung distance: 280 mm
- Ladder width: 420 mm (without stabiliser)
- Maximum load: 150 kg
- nivello® stabiliser with optimum width for the selected product, ensuring an extra safe stance and ascent thanks to nivello® ladder shoes with 2-axis inclination technology, working angle check and exchangeable foot plates. The stabiliser is enclosed separately and is screwed to the lower end of the rail in two places
- Note: In accordance with standards, the attached push-up extension ladder section cannot be separated from the ladder with lengths over 3.0 m

### Scope of supply

- Ladder: 1 x
- Instructions for use and operation: 1 x
- Stabiliser (enclosed separately): 1 x

### Information on sustainability criteria

---

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct

- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

### More product pictures

---



## Added value

---

### Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



### Large range of accessories

- The right equipment for every application
- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders



Optimum and smooth operation, thanks to easily accessible elements

- Simple height adjustment from rung to rung or from step to step
- Wall wheels on the upper part (from 14 rungs or more)
- Fittings with sliding guides
- Smooth-running rope pulley



### nivello® stabiliser

Extra safe, standards-compliant ascent for straight ladders over 3.0 m

- Extra wide stabiliser for even greater stability
- nivello® ladder shoes with patented 2-axis inclination technology, integrated work angle check and exchangeable foot plates
- Individually available as spare part



The movable ladder shoe sets new standards in stability

[Learn more](#)



## Certificates

---



25KFP0347-01 -  
Test Certificate  
"Bauart geprüft"

Valid in



DIN EN 131-1:2019  
DIN EN 131-2:2017  
DIN EN 131-3:2018  
EK5/AK1 17-  
1.3:2021  
PAK-  
ANFORDERUNG  
FÜR GS (PAH  
REQUIREMENT  
FOR GS) AFPS GS  
2019:01 PAK

# Corporate certifications

on sustainability criteria



Management  
System  
ISO 9001:2015  
ISO 14001:2015  
  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548



**Nachhaltigkeit**

**EcoVadis**  
sustainable supply management

CSR-Rating in Silber 2022