



Order no.: 061266

Ladder section anodised aluminium

Length [mm]

1960 2800

3640

Specification

Length	Outer width	Step width	Step/Rung height	Step depth
3.64 m	520 mm	470 mm	30 mm	30 mm
Step/Rung distance	Number of steps/rungs	Depth of side-rails	Max. load capacity	Material
280 mm	13 rungs	60 mm	150 kg	Anodised aluminium
Transport dimensions 3635 x 520 x 60 mm, 6 kg	Business division MUNK Günzburger Steigtechnik	Order no. 061266	Spare part for article no. 500110	Spare part for article no. 500115

Facts

■ Ladder width 520 mm

Rung distance: 280 mm

■ Side-rail dimensions: 60 x 25 mm

■ Dimension of rungs: 30 x 30 mm

Rung design: with anodised aluminium and bright aluminium grooved rungs, with galvanised steel and stainless steel perforated rungs



Scope of supply

Ladder section: 1 x

Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures





Added value

Optimum planning

- Practical planning aids (available as <u>Downloads</u>) with tips for correct planning of vertical ladder systems
- Planning in close coordination with the client as well as the place and purpose of use
- Joint project planning





Corporate certifications

on sustainability criteria







