



Order no.: 052509

Platform ladder, mobile



Number of steps

8

9

11

Specification

Working height 4.1 m	Step design Steps	Number of steps/rungs 9 steps	Platform included as step Yes	Platform height 2.08 m
Step depth 80 mm	Step/Rung distance 235 mm	Height 3.12 m	Base spread 1.57 m	Inclination 70 °
Outer width 650 mm	Stabiliser width 1.55 m	Depth of side-rails 73 mm	Depth of side-rails, support 58 mm	Width of side-rails 25 mm
Max. load capacity 150 kg	Design type Freestanding Single-sided access With chassis beam	Transport dimensions 2930 x 670 x 275 mm, 50 kg	Business division MUNK Günzburger Steigtechnik	Order no. 052509

Facts

- Platform ladder made of aluminium
- Stable rectangular tube side-rails
- Grooved steps with a depth of 80 mm
- Spacious platform with grooves for secure footing (510 x 600 mm)
- 4-fold edged step-to-side-rail connection



- With handrail on both sides, 3-sided, 1,000 mm high railing with knee and foot rails
- Support part with stabilising stabiliser bar for high stability
- Integrated Ø 125 mm fixed castors with locking device for quickly moving to a new location
- nivello® ladder shoes with patented 2-axis inclination technology
- Easy to assemble (delivered unassembled)
- Outer width: 650 mm (without stabiliser)

Step spacing: 235 mmLadder inclination: 70°Maximum load: 150 kg

Scope of supply

Ladder: 1 x

Handrail (enclosed separately): 2 x

Instructions for use and operation: 1 x

Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany



- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard,
 small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Safe working

- Handrails for safe ascent and descent
- Large-format, non-slip platforms
- Conical side-rail guide for safe stance
- Railings and knee boards for safe access and stance



Castors

- Ergonomic and comfortable handling
- Simple movement from place to place



Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



The movable ladder shoe sets new standards in stability

Learn more





Certificates





Corporate certifications

on sustainability criteria







