



Order no.: 052511

Platform ladder, mobile



Number of steps

- 8
- 9
- 11

Specification

|                              |                              |                                                                             |                                                         |                                                      |
|------------------------------|------------------------------|-----------------------------------------------------------------------------|---------------------------------------------------------|------------------------------------------------------|
| Working height<br>4.55 m     | Step design<br>Steps         | Number of steps/rungs<br>11 steps                                           | Platform included as<br>step<br>Yes                     | Platform height<br>2.55 m                            |
| Step depth<br>80 mm          | Step/Rung distance<br>235 mm | Height<br>3.57 m                                                            | Base spread<br>1.78 m                                   | Inclination<br>70 °                                  |
| Outer width<br>650 mm        | Lower outer width<br>1.46 m  | Stabiliser width<br>1.9 m                                                   | Depth of side-rails<br>73 mm                            | Depth of side-rails,<br>support<br>58 mm             |
| Width of side-rails<br>25 mm | Max. load capacity<br>150 kg | Design type<br>Freestanding  <br>Single-sided access  <br>With chassis beam | Transport dimensions<br>3375 x 685 x 295<br>mm, 58.5 kg | Business division<br>MUNK Günzburger<br>Steigtechnik |
| Order no.<br>052511          |                              |                                                                             |                                                         |                                                      |

Facts

- Platform ladder made of aluminium
- Stable rectangular tube side-rails
- Grooved steps with a depth of 80 mm

- Spacious platform with grooves for secure footing (510 x 600 mm)
- 4-fold edged step-to-side-rail connection
- With handrail on both sides, 3-sided, 1,000 mm high railing with knee and foot rails
- Support part with stabilising stabiliser bar for high stability
- Integrated Ø 125 mm fixed castors with locking device for quickly moving to a new location
- nivello® ladder shoes with patented 2-axis inclination technology
- Easy to assemble (delivered unassembled)
- Outer width: 650 mm (without stabiliser)
- Step spacing: 235 mm
- Ladder inclination: 70°
- Maximum load: 150 kg

### Scope of supply

- Ladder: 1 x
- Handrail (enclosed separately): 2 x
- Instructions for use and operation: 1 x

### Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems

- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures

---



## Added value

---

### Safe working

- Handrails for safe ascent and descent
- Large-format, non-slip platforms
- Conical side-rail guide for safe stance
- Railings and knee boards for safe access and stance



### Castors

- Ergonomic and comfortable handling
- Simple movement from place to place



### Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



The movable ladder shoe sets new standards in stability

[Learn more](#)



## Certificates

---



5011053.24003 -  
Certificate Product  
Safety Type  
approved

Valid in



DIN EN 131-7:2013  
DIN EN 131-3:2018

## Corporate certifications

on sustainability criteria



Management  
System  
ISO 9001:2015  
ISO 14001:2015  
  
www.tuv.com  
ID 9108612548



**Nachhaltigkeit**

**EcoVadis**  
sustainable supply management

CSR-Rating in Silber 2022