



Order no.: 011216

Roof hooks for plain tiles galvanised steel

Model versions

Anthracite grey powder-coated

Brown powder-coated

Red powder-coated

Red-brown powder-coated

Galvanised steel

Specification

Colour version Galvanised steel	Transport dimensions 425 x 210 x 30 mm, 1.08 kg	Business division MUNK Günzburger Steigtechnik	Order no. 011216
------------------------------------	---	--	---------------------

Facts

- Delivery includes with grooved nails
- Coloured hooks are hot-dip galvanised and powder-coated
- To be mounted centrally on the rafters
- At least two hooks are needed for the first ladder and at least one hook is needed for each additional ladder
- Complies with Construction Products Ordinance (BauPVO) 305/2011 (EU) and DIN EN 517
- Safety roof hooks in accordance with DIN EN 517 must be installed on roofs with an inclination of 22.5° to 75°. They must be distributed over the roof surface as follows:
 - Upper row < 1.0 m below the ridge
 - Intermediate rows in each case < 5.0 m distance from the row above

- Lower row < 1.5 m above the eaves, in each case measured in the roof pitch
- The horizontal distance between the safety hooks of a row must not exceed 2.0 m. To be used for eaves heights above 3.0 m

Scope of supply

- Roof hooks: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Industrial grade

Stable and robust for tough everyday working life
(including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



Corporate certifications

on sustainability criteria



Management
System
ISO 9001:2015
ISO 14001:2015

www.tuv.com
ID 9108612548



Nachhaltigkeit

EcoVadis
sustainable supply management

CSR-Rating in Silber 2022