



Order no.: 063271

Special wall bracket, adjustment range 600-700mm, galvanised steel

Wall clearance min [mm]

500



700 800

Specification

Wall distance	Wall anchor	Wall distance min.	Wall distance max.	Adjustment range
600 mm	Single	600 mm	700 mm	100 mm
Material Galvanised steel	Transport dimensions 610 x 200 x 200 mm, 11.5 kg	Business division MUNK Günzburger Steigtechnik	Order no. 063271	

Facts

- Available for wall clearances of 500-900 mm
- Good anchoring for different wall types
- Steel quality ensures a high load-bearing capacity
- 1 set comprising 1x right, 1x left

Scope of supply

Wall anchor: 2 x



Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

RoHS

■ REACH

The MUNK Group complies with a Code of Conduct

The Supply Chain Act does not apply due to our size

The materials used are listed in the technical specification

Resource-saving production: own photovoltaic systems

Energy-efficient consumption during production: LED lighting

Repairability, durability and quality: 15-year warranty on series products made in Germany

- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures







Added value

Optimum planning

- Practical planning aids (available as <u>Downloads</u>) with tips for correct planning of vertical ladder systems
- Planning in close coordination with the client as well as the place and purpose of use
- Joint project planning





Corporate certifications

on sustainability criteria







