

Order no.: 052525

Platform ladder FlexxStep



Number of rungs

- 4
- 5
- 6

Specification

Working height 3.3 m	Step design Rungs	Number of steps/rungs 5 rungs	Platform included as step Yes	Platform height 1.28 m
Platform length 655 mm	Platform width 480 mm	Step/Rung height 30 mm	Step depth 30 mm	Step/Rung distance 280 mm
Base spread 1.35 m	Inclination 70 °	Outer width 672 mm	Width incl. extension arm 1.98 m	Depth of side-rails 58 mm
Width of side-rails 25 mm	Castor diameter 150 mm	Max. load capacity 150 kg	Design type Freestanding Single-sided access With castors	Transport dimensions 2735 x 760 x 390 mm, 29 kg
Business division MUNK Günzburger Steigtechnik	Order no. 052525			

Facts

- Platform ladder made of aluminium
- Stable rectangular tube side-rails

- Rectangular rungs grooved on both sides, 30 x 30 mm
- Spacious platform made of grooved aluminium chequered plate 480 x 655 mm
- 4-fold edged rung-to-side-rail connection
- With handrail on both sides, 3-sided, 1,000 mm high railing with knee and foot rails
- Infinitely variably adjustable outriggers on both sides
- Automatically closing safety door
- Generous sized tool tray
- Two Ø 150 mm castors and practical folding mechanism for quickly moving to a new location
- Available with and without flexible telescopic push-fit attachment
- Design compliant DIN EN 131-7 and the French standards NFP 93-352/353
- Maximum load: 150 kg

Scope of supply

- | | |
|---------------------------------------|------------------------------|
| ■ Ladder: 1 x | ■ Security door: 1 x |
| ■ Handrail (enclosed separately): 2 x | ■ Installation material: 1 x |
| ■ Castor (enclosed separately): 2 x | ■ Assembly instructions: 1 x |

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size

- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Safe working

- Handrails for safe ascent and descent
- Large-format, non-slip platforms
- Conical side-rail guide for safe stance
- Railings and knee boards for safe access and stance



Storage tray

- For the practical storage of small parts
- Made from high-quality plastic
- Partly with integrated hooks and tool holders
- Different versions, depending on the ladder model



Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



Castors

- Ergonomic and comfortable handling
- Simple movement from place to place



Corporate certifications

on sustainability criteria



Management
System
ISO 9001:2015
ISO 14001:2015

www.tuv.com
ID 9108612548



Nachhaltigkeit

EcoVadis
sustainable supply management

CSR-Rating in Silber 2022