



Order no.: 052535

FlexxStep platform ladder 5 rungs with telescopic attachment 2 rungs





Number of rungs

 $6 + 2 \quad 6 + 3$

Specification

| Step design Rungs | Number of steps/rungs 5 + 2 rungs | Platform included as step Yes | Platform height 1.84 m | Step/Rung height 30 mm |
|--|--|-------------------------------------|---|---|
| Step depth 30 mm | Step/Rung distance 280 mm | Inclination 70 ° | Outer width 672 mm | Depth of side-rails 58 mm |
| Width of side-rails 25 mm | Castor diameter 150 mm | Max. load capacity 150 kg | Design type Free-standing Single-sided access With castors Flexible | Transport dimensions 2735 x 760 x 390 mm, 29 kg |
| Transport dimensions 2 1145 x 565 x 105 mm, 6 kg | Business division MUNK Günzburger Steigtechnik | Order no. 052535 | T TOAIDIG | |

Facts

- Platform ladder made of aluminium
- Stable rectangular tube side-rails
- Rectangular rungs grooved on both sides, 30 x 30 mm
- Spacious platform made of grooved aluminium chequered plate 480 x 655 mm



- 4-fold edged rung-to-side-rail connection
- With handrail on both sides, 3-sided, 1,000 mm high railing with knee and foot rails
- Infinitely variably adjustable outriggers on both sides
- Automatically closing safety door
- Generous sized tool tray
- Integrated Ø 150 mm castors and practical folding mechanism for quickly moving to a new location
- Design compliant DIN EN 131-7 and the French standards NFP 93-352/353
- Height-adjustable and suitable for stairs by means of telescopic outrigger that can be mounted without tools
- Maximum load: 150 kg

Scope of supply

Ladder: 1 x

Instructions for use and operation: 1 x

Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany



- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures









Added value

Safe working

- Handrails for safe ascent and descent
- Large-format, non-slip platforms
- Conical side-rail guide for safe stance
- Railings and knee boards for safe access and stance



Storage tray

- For the practical storage of small parts
- Made from high-quality plastic
- Partly with integrated hooks and tool holders
- Different versions, depending on the ladder model



Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



Castors

- Ergonomic and comfortable handling
- Simple movement from place to place





Sponsored by BG BAU

Specification subject to conditions; for the latest information please visit the BG BAU website (statutory accident insurance company for the construction and construction related services in Germany). Since 2014, the BG BAU has been promoting the purchase of platform ladders, step stools and ladder accessories with single-sided and double-sided access. All members of the BG BAU profit from this. This aims to prevent work accidents on building sites and improve ergonomic working practices. For more information by BG BAU, please visit:

www.bgbau.de/service/angebote/arbeitsschutzpraemien

A brief overview of the subsidy and an overview of our eligible products can be found on our website under know-how.



Corporate certifications

on sustainability criteria







